




LMI TECHNOLOGIES

FactorySmart® Inspection



# A PROVEN LEADER IN 3D SCANNING AND INSPECTION

FOR THE RUBBER AND TIRE INDUSTRIES

**Gocator.**

## CONTENTS

- 3** Welcome to FactorySmart®
- 4** The Challenges of Rubber & Tire Inspection
- 5** Achieve Your Manufacturing Goals
- 6** Gocator® for Smart R&T Inspection
- 7** Realize the Benefits of Smart 3D
- 8** Tire Building Inspection – Rubber Extrusion Profiling
- 9** Strip Guidance and Splice Control
- 10** Layer Control
- 11** Finished Tire Inspection – Bulge and Dent, Radial and Lateral Runout
- 12** Tire Markings and DOT-Code Identification
- 13** Gocator Firmware: Built-In Measurement Tools

# WELCOME TO FACTORYSMART®

## Advanced 3D Quality Control for Rubber & Tire

LMI Technologies designs and supplies high-performance, non-contact, all-in-one 3D scanning solutions for critical rubber and tire inspection applications such as rubber extrusion profiling, strip guidance, splice and layer control, bulge and dent inspection, radial and lateral runout, tire markings and DOT-code identification.


### TIRE BUILDING INSPECTION

#### RUBBER EXTRUSION PROFILING




Gocator provides a complete set of built-in extrusion measurement tools that include functions such as length, width, height, depth, angle, vertex location, and groove dimension.

#### STRIP GUIDANCE




As tire strips (or plies) are wound around the drum of the tire, Gocator scans the strip edges to ensure they are fed to the correct position.

#### SPLICE CONTROL



During tire assembly, Gocator is used to detect problems with joints in splicing and stitching such as gaps, overlaps, dog ears, and folded material.

#### LAYER CONTROL



Gocator scans for the presence, width, and overlap position of key components, looking for gaps between layered gum rubber strips and flat rubber sheets that make up the body of the tire.


### FINISHED TIRE INSPECTION

#### BULGE AND DENT




Gocator sensors provide full 3D surface data to detect small bulges and dents on tire sidewall surfaces.

#### RADIAL AND LATERAL RUNOUT



Gocator inspects for radial runout (RRO) and lateral runout (LRO) by taking profile measurements at the tire's centerline and shoulders. These measurements indicate the deviation of the tire's roundness from a perfect circle and identify potential spin problems such as "hop" and "wobble".

#### TIRE MARKINGS



Gocator scans painted or laser tire markings on the sidewall of the tire, including values such as tire size and maximum inflation pressure. Gocator generates an intensity image of the marking that is then processed using HexSight or Gocator SDK.


#### DOT-CODE IDENTIFICATION



Gocator produces a height-map image of embossed, black-on-black sidewall characters for analysis and conversion to alphanumeric data.

# CHALLENGES OF RUBBER & TIRE INSPECTION

Rubber and tire production presents a unique set of challenges due to the nature of the materials involved.



## High-Speed Inspection of Dark Materials

R&T applications involve scanning low-contrast, dark materials with complex geometry at very high speed. From shiny green rubber surfaces to hard-to-scan black-on-black DOT-codes, ensuring 100% quality control requires a 3D scanning solution.


## The Limitations of 2D

2D machine vision relies on contrast to detect features. 3D relies on shape. Scanning black features on a black tire is a natural application for 3D. With shape, 3D can measure critical features such as object flatness and surface geometry.

# ACHIEVE YOUR MANUFACTURING GOALS


These are the goals you need to reach to improve your factory production.

- » Speed up inspection cycle times
- » Ensure quality tire production
- » Generate less waste/rework of material
- » Reduce exposure to product recalls
- » Increase manufacturing flexibility  
(e.g., multiple models/sizes of tires)



# GOCATOR® FOR SMART R&T INSPECTION

Gocator 3D smart sensors improve factory production by providing a complete solution for 3D scanning, measurement, and control in high-speed, low-contrast R&T applications.



## Complete 3D Inspection. Built-In.

Inspection is a multi-step process. First, the target is digitized in 3D. Then it's measured to verify critical tolerances are met. Finally a control decision is communicated—either to a robot, PLC, or factory process control monitoring systems. What makes Gocator smart is that all of these capabilities are onboard, minimizing system cost and complexity and helping manufacturers achieve 100% quality control.

## Quality Control Decision-Making

Gocator makes critical pass/fail decisions and communicates these directly to factory networks and equipment—all within a single package, and all at production speed.

## Designed for High-Speed R&T Applications

Gocator line profilers have a 2-megapixel imager that delivers high-resolution profiles at 5 kHz—making them ideal for any high-speed scanning task, including tread/sidewall, rubber extrusion, and more. Faster scanning allows users to speed up their inline process and achieve the highest resolutions.

## Gocator Firmware and HexSight

Every Gocator comes with proprietary built-in measurement tools. You can also extend your Gocator packaging inspection system with HexSight's integrated, robust 2D machine vision library for Optical Character Recognition (OCR).



# REALIZE THE BENEFITS OF SMART 3D

Gocator makes production FactorySmart®.

## Web-Based User Interface

Gocator offers an easy-to-use web-based user interface that requires no special training. Simply open your favorite web browser to access and control the Gocator. Leverage a point-and-click design with effective 3D visualization using responsive pan, zoom, and rotate navigation.

## Flexible Design for Multi-Model Production

Gocator 3D smart sensors can be “reprogrammed” on-the-fly by loading different “job” files that correspond to each model in a multi-model production line. A job file contains the specific settings for measurements, exposures, and pass/fail criteria.

## Network Connected

Gocator can adapt to changing inspection requirements because it is connected to the factory network, and can easily be updated with new firmware. New firmware can introduce custom measurement tools developed by the process engineering group overseeing the factory environment so that a new process or part receives proper inspection.

## Scalable

Gocator laser profilers support seamless multi-sensor networking for scanning large or complex objects (i.e., with irregular surface geometry and multiple occlusions). These sensor networks are connected by LMI Master controllers.

## WHY YOU NEED SMART 3D:

- » Volumetric measurement (X, Y, and Z axis) provides shape and position related parameters
- » Contrast invariant, ideal for inspecting low contrast objects
- » Immune to lighting variation and ambient light
- » Higher repeatability due to integrated optics, lighting, and factory pre-calibration
- » Simpler to build multi-sensor setups for large object inspection



# GOCATOR LASER PROFILERS

## for Rubber Extrusion Profiling


Fast, High-Density Contour Measurement Profiles

### Rubber Extrusion Profiling

Measurement of a tire's extrusion groove pattern, geometry, and location is very challenging to achieve at production speed. The task of gauging extrusions is made even more complex by frequent product changeover. This means an effective inline scanning and inspection solution must deliver the high scan speed and measurement flexibility required to achieve maximum finished tire quality and minimize material scrap.

### The Smart 3D Solution

Gocator 3D smart sensors deliver high-speed, high-density contour measurement, even from the highly reflective shiny black surfaces of "green" tires. What's more, Gocator offers a powerful dedicated Groove measurement tool designed expressly for extrusion measurement applications. This built-in, user-configurable tool includes measurement functions such as length, width, height, depth, angle, vertex location, groove dimension, and many other tire metrology requirements.



### **GOCATOR® IS FLEXIBLE:**

- » Supports inspection of multiple grooves in a single setup
- » Groove measurements unaffected by changes in surface angle relative to the sensor
- » For wider extrusions, multiple sensors can be networked for larger field of view
- » Measurement values can be communicated over factory networks using Gigabit Ethernet



# GOCATOR LASER PROFILERS

## for Strip Guidance and Splice Control

3D Tread Length, Width, Depth, Profile, and Splice

### Strip Guidance

As different types of tire strips (e.g., body plies, gum strips, band bead filler strips) are wound around the drum of the tire, Gocator scans the strip edges to ensure they are in the correct position. Its built-in measurement tools for strip positions—including multiple groove location, depth measurement monitoring, and automated alignment—enable users to configure setup parameters without requiring any additional measurement software development.

### Splice Control

During tire assembly, Gocator 3D smart sensors are used to detect splicing and stitching issues such as gaps, faulty overlaps, dog ears, and material that's folded back on itself.



Gaps

Dog ears




Blisters

Holes



Faulty overlaps

Folds



Grooves

Strips

Peaks and valleys

Belt plies

Wrinkles

**GOCATOR® IS SPECIALIZED:**

- » Built-in tools for strip and groove measurement
- » Ability to store multiple geometry configurations
- » No additional software development required


# GOCATOR LASER PROFILERS

## for Layer Control

Fast, High-Density Profile Measurement

### Layer Control

Gocator 3D smart sensors scan for the presence, width, and overlap position of key components such as gum rubber strips and layered flat rubber sheets that make up the body of the tire. In order to take layer measurements, Gocator scans a raised line extruded into the rubber that serves as a reference point for guiding and positioning additional layers of rubber material. Scanning this extruded edge requires Gocator's 3D depth measurement.



### USE GOCATOR FOR:

- » Bank and stop gap calender roll inspection
- » Feed bandwidth and thickness inspection
- » Groove/embossing depth measurement
- » Cap and steel ply inspection
- » Rib and shoulder inspection



### SDK for Smarter Tire Inspection

The SDK (Software Development Kit) provides complete control and management of your Gocator sensor in order to fit your specific application needs. You can use the Gocator SDK to create network TCP/IP connections, stream data into circular buffers, parse XML settings, and manage multiple threads. With open source C-based code provided, it's easy to program exactly how Gocator acquires and processes data on any computer or mobile device of your choice.


# GOCATOR LASER PROFILERS

## for Finished Tire Inspection

Complete 3D Surface Data



### Bulge and Dent

Final tire geometry systems need to detect bulges and dents as small as 25  $\mu\text{m}$ , which indicate critical internal defects that may lead to tire failure. These imperfections can occur anywhere on the tire sidewall or tread. To increase quality and improve product safety, small areas of dimensional variation or defects must be detected with submillimeter accuracy and reliability. Cycle time is also critical for final inspection, requiring full surface inspection in one revolution to meet strict throughput requirements.



### Radial and Lateral Runout



Radial runout occurs when the radius of the tire is not consistent from the wheel midpoint to any point on the rim. Too much radial runout can cause up and down vibrations, or “hopping”, when the tire spins. Lateral runout is the amount of sideways motion, or “wobble”, in a tire as it rotates.



Radial runout

### The Smart 3D Solution

With rapid scan speed and real-time data acquisition, Gocator provides full 3D surface data to detect small defects anywhere on the sidewall surface and tire tread, meeting demanding cycle time requirements. A typical Gocator tire inspection system includes three profile sensors: one for profiling each sidewall, and a third for monitoring radial and lateral runout of the tread.



Lateral runout



### CASE STUDY:

#### CTI Uses Gocator in Its Tire Uniformity Optimization Systems

Faced with the challenge of upgrading their old capacitive sensors, CTI introduced Gocator into select TUO systems. Gocator gives CTI's system a greater volume of tire data and its unique all-in-one 3D scanning and inspection functionality minimizes component and system complexity, improves reliability, maximizes robustness and repeatability, and makes system integration faster, easier and more cost-effective than any other 3D scanning and inspection solution on the market.

# GOCATOR LASER PROFILERS

## for Tire Markings and DOT-Code Identification

Height Map Imaging for Automated Code Recognition

### Tire Markings


Gocator scans painted or lasered tire markings on the sidewall of the tire, including tire size and maximum inflation pressure. It achieves this measurement by generating an intensity image of the marking that is then processed using HexSight or Gocator SDK.

### DOT-Code Identification

Tire sidewalls contain extensive alphanumeric information in the form of raised or embossed characters. These include tire identification codes for sorting and DOT-codes for tracking the vehicle identification number at the time of assembly. The common industry solution of reading alphanumeric characters with 2D imaging and optical character recognition software is insufficient for tire sidewalls because the raised or embossed characters are “black-on-black”, with effectively zero contrast.

### The Smart 3D Solution

Gocator solves this challenge by generating an image of embossed characters as a height map. Its native GenTL driver sends the height-map data to compliant third-party software for automated character recognition. When tires are rotating, such as in uniformity inspection systems, Gocator supports triggering by a quadrature encoder, stamping each profile with a Z position index value. This allows seamless scan alignment across multiple sensors.



An example of automatic reading of DOT codes is shown above. The upper image is a scan of the tire sidewall (flattened), and the lower image shows the 3D height map of the DOT-code, with the alphanumeric code as read superimposed below the characters.

# GOCATOR FIRMWARE


## Built-In Measurement Tools for Efficient Tire Inspection

Application-Specific Tools Make Measurement Fast and Easy



### Built-In Profile Measurement Tools

Gocator provides a full selection of built-in rubber and tire inspection measurement tools for key features such as width, length, distance between points, positions, angles, profile C/S area, grooves, multiple strips, and more.



### Built-In Surface Measurement Tools


Gocator has volumetric measurement tools for evaluating 3D geometry such as area, volume, and centroids.

### GOCATOR® IS SMART:

- » Rapid scan speeds of 5 kHz
- » Buffered, real-time processing ensures no lost data
- » Pre-calibrated to measure out-of-the-box for a selected measurement volume
- » Provides optimized exposure setting
- » Ability to easily set decision thresholds
- » Ease-of-integration results in faster setup and lower system costs

# LMI TECHNOLOGIES

What makes LMI different from catalogue-based companies is that **our sole focus is 3D technology**. Four pillars support this specialized approach and drive our commitment to accelerate customer profitability by delivering the highest performing and most cost-effective 3D scanning and inspection solutions.



## Chip-Level Engineering

We design and deliver proven 3D technologies at the lowest cost.



## Smart Technology

Smart sensors run standalone to produce inspection solutions out-of-the-box.



## Simple User Experience

You don't need to be a rocket scientist to use our products—just point and click.



## Progressive Partnerships

We build OEM solutions in support of our long-term partnerships.

“

LMI provides OEMs with a flexible 3D technology platform that can be customized to meet their unique business demands. Unlike our competitors, 3D scanning and inspection is all we do, and it is this specialized knowledge and experience that helps drive profitability, reduce time to market, and open up new possibilities for our clients.

Terry Arden, CEO

”



**It's Better to Be Smart.**

[contact@lmi3d.com](mailto:contact@lmi3d.com) | [lmi3d.com](http://lmi3d.com)

---

**AMERICAS**

LMI Technologies Inc.  
Burnaby, BC, Canada

**EMEAR**

LMI Technologies GmbH  
Teltow/Berlin, Germany

**ASIA PACIFIC**

LMI (Shanghai) Trading Co., Ltd.  
Shanghai, China



LMI Technologies has offices worldwide. All contact information is listed at [lmi3d.com/contact](http://lmi3d.com/contact)